

Needle roller bearing 20NQ3315D-JTEKT - 20NQ3315D-JTEKT

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/20nq3315d-jtekt>

Machined ring needle roller bearings Koyo
F_W 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F _w	d	D	B	C _r	C _{0r}	Oil lub.	Without inner ring	
20	—	33	15	14.0	16.9	21 000	20NQ3315D	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
With inner ring				Without inner ring	With inner ring			
	d _a	D _a	r _a	0.052	—			
	min.	max.	max.	—	—			
	—	29	0.6					

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952477473
Inside diameter	20 mm
Inside diameter	0.787" inch
Outside diameter	33 mm
Outside diameter	1.299" inch
Thickness	15 mm
Thickness	0.591" inch
Weight	52 g
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE