

## Needle roller bearing NQ16-20-JTEKT - NQ16-20-JTEKT

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/nq16-20-jtekt>

Machined ring needle roller bearings ————— **Koyo**  
F<sub>W</sub> 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No. Without inner ring
F <sub>w</sub>	d	D	B	C <sub>r</sub>	C <sub>0r</sub>	Oil lub.			
16	—	24	20	—	13.1	19.1	28 000	<b>NQ16/20</b>	
Mounting dimensions (mm)				Mass (kg)		Applicable inner ring No.			
With inner ring				d <sub>i</sub> max.	D <sub>o</sub> max.	r <sub>s</sub> max.	Without inner ring	With inner ring	
				—	22	0.3	0.032	—	

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952477701
Inside diameter	16 mm
Inside diameter	0.63" inch
Outside diameter	24 mm
Outside diameter	0.945" inch
Thickness	20 mm
Thickness	0.787" inch
Weight	32 g
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE