


## Tapered roller bearing 45322-JTEKT - 45322-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/45322-jtekt>

Double-row tapered roller bearings TDI type Koyo



Boundary dimensions (mm)						Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
d	D	B	T	r	r <sub>1</sub>	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.
110	180	56	56	2	2.5	300	505	1 600	2 100

Bearing No.	Mounting dimensions (mm)						Constant e	Axial load factors			(Refer.) Mass (kg)
	d <sub>a</sub> max.	D <sub>a</sub> max.	D <sub>a</sub> min.	S <sub>a</sub> min.	r <sub>a</sub> max.	r <sub>b</sub> max.		Y <sub>2</sub>	Y <sub>3</sub>	Y <sub>0</sub>	
45322	128	170	160	4	2	2	0.35	1.95	2.90	1.91	5.40

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250130632
Inside diameter	110 mm
Outside diameter	180 mm
Thickness	56 mm
Weight	5400 g
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE