

Tapered roller bearing 45228-JTEKT - 45228-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/45228-jtekt>

Double-row tapered roller bearings
TDI type Koyo



| Boundary dimensions (mm) | | | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | |
|--------------------------|-----|----|----|---|----------------|-------------------------|-----------------|--------------------------------------|----------|
| d | D | B | T | r | r ₁ | C _r | C _{0r} | Grease lub. | Oil lub. |
| 140 | 210 | 53 | 53 | 2 | 2.5 | 311 | 564 | 1300 | 1800 |

| Bearing No. | Mounting dimensions (mm) | | | | | | Constant e | Axial load factors | | | (Refer.) Mass (kg) |
|-------------|--------------------------|----------------------|----------------------|----------------------|----------------------|----------------------|------------|--------------------|----------------|----------------|--------------------|
| | d _{1a} max. | D _{1a} max. | D _{1a} min. | S _{1a} min. | r _{1a} max. | r _{1b} max. | | Y ₂ | Y ₃ | Y ₀ | |
| 45228 | 159 | 200 | 188 | 4 | 2 | 2 | 0.27 | 2.47 | 3.67 | 2.41 | 6.45 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 4549250130472 |
| Inside diameter | 140 mm |
| Outside diameter | 210 mm |
| Thickness | 53 mm |
| Weight | 6450 g |
| Packaging | 1 |

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE