


Tapered roller bearing 45372-JTEKT - 45372-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/45372-jtekt>

Double-row tapered roller bearings
TDI type Koyo



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds (min ⁻¹)		
<i>d</i>	<i>D</i>	<i>B</i>	<i>T</i>	<i>r</i> max.	<i>r</i> min.	<i>C_r</i>	<i>C_{0r}</i>	Grease lub.	Oil lub.
360	600	192	192	5	6	3 360	6 750	360	490

Bearing No.	Mounting dimensions (mm)					Con- stant <i>e</i>	Axial load factors			(Refer.) Mass (kg)	
	<i>d_a</i> max.	<i>D_a</i> max.	<i>D_a</i> min.	<i>S_a</i> min.	<i>r_a</i> max.		<i>Y₂</i>	<i>Y₃</i>	<i>Y₀</i>		
45372	419	578	528	10	4	5	0.32	2.12	3.15	2.07	228

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952482095
Inside diameter	360 mm
Outside diameter	600 mm
Thickness	192 mm
Weight	228000 g
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE