


Tapered roller bearing 45284-JTEKT - 45284-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/45284-jtekt>

Double-row tapered roller bearings
TDI type Koyo



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds (min ⁻¹)		
<i>d</i>	<i>D</i>	<i>B</i>	<i>T</i>	<i>r</i> max.	<i>r</i> min.	<i>C_r</i>	<i>C_{0r}</i>	Grease lub.	Oil lub.
420	620	150	150	5	6	2 800	5 200	320	430

Bearing No.	Mounting dimensions (mm)					Con- stant <i>e</i>	Axial load factors				(Refer.) Mass (kg)
	<i>d_a</i> max.	<i>D_a</i> max.	<i>D_a</i> min.	<i>S_a</i> min.	<i>r_a</i> max.		<i>Y₂</i>	<i>Y₃</i>	<i>Y₀</i>		
45284	475	598	564	6	4	5	0.33	2.03	3.02	1.98	152

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250130533
Inside diameter	420 mm
Inside diameter	16.535" inch
Outside diameter	620 mm
Outside diameter	24.409" inch
Thickness	150 mm
Thickness	5.906" inch
Weight	152000 g
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE