


## Tapered roller bearing 452-500-JTEKT - 452-500-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/452-500-jtekt>

Double-row tapered roller bearings  
TDI type Koyo



Boundary dimensions (mm)						Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
<i>d</i>	<i>D</i>	<i>B</i>	<i>T</i>	<i>r</i> max.	<i>r</i> min.	<i>C<sub>r</sub></i>	<i>C<sub>0r</sub></i>	Grease lub.	Oil lub.
500	720	167	167	6	6	3 430	7 350	250	330

Bearing No.	Mounting dimensions (mm)					Con- stant <i>e</i>	Axial load factors			(Refer.) Mass (kg)	
	<i>d<sub>a</sub></i> max.	<i>D<sub>a</sub></i> max.	<i>D<sub>a</sub></i> min.	<i>S<sub>a</sub></i> min.	<i>r<sub>a</sub></i> max.		<i>Y<sub>2</sub></i>	<i>Y<sub>3</sub></i>	<i>Y<sub>0</sub></i>		
452/500	545	692	645	8	5	5	0.39	1.74	2.59	1.70	222

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952482224
Inside diameter	500 mm
Outside diameter	720 mm
Thickness	167 mm
Weight	222000 g
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE