

## Roller bearing NQ28-30-JTEKT - NQ28-30-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/roller/nq28-30-jtekt>

### Machined ring needle roller bearings Koyo

$F_w$  29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.
$F_w$	d	D	B	$C_r$	$C_{10}$	Oil lub.	With inner ring	Without inner ring	
28	—	37	30	—	29.1	54.1	16 000	—	NQ28/30
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
With inner ring				Without inner ring	With inner ring				
	$d_1$	$D_1$	$r_1$	0.083	—				
	max.	max.	max.	—	—				

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952482521
Inside diameter	28 mm
Outside diameter	37 mm
Thickness	30 mm
Weight	83 g
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE