

## Roller bearing NQ29-30-JTEKT - NQ29-30-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/roller/nq29-30-jtekt>

Machined ring needle roller bearings ————— **Koyo**  
F<sub>w</sub> 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.	
F <sub>w</sub>	d	D	B	C <sub>r</sub>	C <sub>0r</sub>	Oil lub.	Without inner ring		
29	25	38	30	28.9	54.3	16 000	NQ29/30		
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
With inner ring				Without inner ring	With inner ring				
d <sub>2</sub>	D <sub>2</sub>	r <sub>a</sub>		0.085	0.125				
min.	max.	max.							
27	36	0.3							

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952482620
Inside diameter	29 mm
Inside diameter	1.142" inch
Outside diameter	38 mm
Outside diameter	1.496" inch
Thickness	30 mm
Thickness	1.181" inch
Weight	85 g
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE