


Roller bearing NA4906UU-JTEKT - NA4906UU-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/roller/na4906uu-jtekt>

Machined ring needle roller bearings Koyo

F_w 29 ~ 37 mm

With inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No. Without inner ring	
F_w	d	D	B	C_r	C_{10}	Oil lub.			
35	30	47	17	18	0.3	19.5	25.3	5 700	—
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
With inner ring				Without inner ring	With inner ring				
	d_a	D_a	r_a						
	max.	max.	max.						
	NA4906UU	32	45	0.3	—	0.105	IRM303518		

[Note] 1) Limiting speeds of bearing number NA49...UU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952482873
Inside diameter	30 mm
Outside diameter	47 mm
Thickness	17 mm
Weight	105 g
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE