


Roller bearing NA4906R-JTEKT - NA4906R-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/roller/na4906r-jtekt>

Machined ring needle roller bearings Koyo

F_w 29 – 37 mm

With inner ring



| Boundary dimensions (mm) | | | | | Basic load ratings (kN) | | Limiting speeds ¹⁾ (min ⁻¹) | | Bearing No. | |
|--------------------------|----|----|----|-------|-------------------------|-----------------|--|-------|--------------------|-----------|
| F_w | d | D | B | B_1 | C_r | C_{10} | Oil lub. | | Without inner ring | |
| 35 | 30 | 47 | 17 | | 26.4 | 34.4 | 13 000 | | — | |
| Mounting dimensions (mm) | | | | | Inner Mass (kg) | | Applicable inner ring No. | | | |
| With inner ring | | | | | Without inner ring | With inner ring | | | | |
| NA4906R | | | | | 32 | 45 | 0.3 | 0.070 | 0.103 | IRM303517 |

[Note] 1) Limiting speeds of bearing number NA49...JU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 3663952482910 |
| Inside diameter | 30 mm |
| Outside diameter | 47 mm |
| Thickness | 17 mm |
| Weight | 103 g |
| Packaging | 1 |

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE