


## Roller bearing NQI35-30-JTEKT - NQI35-30-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/roller/nqi35-30-jtekt>

### Machined ring needle roller bearings Koyo

$F_w$  29 ~ 37 mm

With inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.
$F_w$	d	D	B	$C_r$	$C_{10}$	Oil lub.	Without inner ring	
40	35	50	30	39.8	79.8	12 000	—	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
With inner ring				Without inner ring	With inner ring	—		
NQI35/30				37	48	0.3	0.120	0.192

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952483061
Inside diameter	35 mm
Outside diameter	50 mm
Thickness	30 mm
Weight	192 g
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE