


## Roller bearing NQI40-30-JTEKT - NQI40-30-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/roller/nqi40-30-jtekt>

### Machined ring needle roller bearings Koyo

$F_w$  29 – 37 mm

With inner ring



| Boundary dimensions (mm) |    |    |    | Basic load ratings (kN) |                 | Limiting speeds <sup>1)</sup> (min <sup>-1</sup> ) |                    | Bearing No. |
|--------------------------|----|----|----|-------------------------|-----------------|--|--------------------|-------------|
| $F_w$                    | d  | D  | B  | $C_r$                   | $C_{0r}$        | Oil lub.   | Without inner ring |             |
| 45                       | 40 | 55 | 30 | 40.9                    | 86.1            | 10 000   | —                  |             |
| Mounting dimensions (mm) |    |    |    | (Refer.) Mass (kg)      |                 | (Refer.) Applicable inner ring No.                 |                    |             |
| With inner ring          |    |    |    | Without inner ring      | With inner ring | —  |                    |             |
| NQI40/30                 |    |    |    | 44                      | 51              | 0.138  | 0.214              | —           |

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## PRODUCT FEATURES

|                  |              |
|------------------|--------------|
| Brand            | JTEKT        |
| N° Ean13         | 605790188039 |
| Inside diameter  | 40 mm        |
| Outside diameter | 55 mm        |
| Thickness        | 30 mm        |
| Weight           | 214 g        |
| Packaging        | -            |

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE