


## Roller bearing NA5920-JTEKT - NA5920-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/roller/na5920-jtekt>

Machined ring needle roller bearings Koyo

$F_w$  29 ~ 37 mm

With inner ring



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.	
$F_w$	$d$	$D$	$B$	$B_1$	$C_r$	$C_{10}$	Oil lub.		Without inner ring	
115	100	140	54		189.0	418.0	4 000		—	
Mounting dimensions (mm)					(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
With inner ring					Without inner ring	With inner ring				
NA5920					106.5	133.5	1	1.49	2.53	IRM1001554

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952484242
Inside diameter	100 mm
Outside diameter	140 mm
Thickness	54 mm
Weight	2530 g
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE