

## Deep groove ball bearing single row W603-ZZX-JTEKT - W603-ZZX-JTEKT

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/single-row/w603-zzx-jtekt>

Boundary dimensions

Open type    Shielded    Sealed    Locating snap ring

ZZ / 2Z / 2RS / 2RD    NR

300 / 350 / 400 / 450 / 500 / 550 / 600 / 650 / 700 / 750 / 800 / 850 / 900 / 9500 / 10000 / 15000 / 20000 / 30000 / 40000 / 50000 / 60000

Extra small diameters: 10 / 12 / 15 / 17 / 19 / 22 / 24 / 26 / 28 / 30 / 32 / 34 / 36 / 38 / 40 / 42 / 44 / 46 / 48 / 50

Extra large diameters: 110 / 120 / 130 / 140 / 150 / 160 / 170 / 180 / 190 / 200 / 210 / 220 / 230 / 240 / 250 / 260 / 270 / 280 / 290 / 300 / 310 / 320 / 330 / 340 / 350 / 360 / 370 / 380 / 390 / 400 / 410 / 420 / 430 / 440 / 450 / 460 / 470 / 480 / 490 / 500 / 510 / 520 / 530 / 540 / 550 / 560 / 570 / 580 / 590 / 600 / 610 / 620 / 630 / 640 / 650 / 660 / 670 / 680 / 690 / 700 / 710 / 720 / 730 / 740 / 750 / 760 / 770 / 780 / 790 / 800 / 810 / 820 / 830 / 840 / 850 / 860 / 870 / 880 / 890 / 900 / 910 / 920 / 930 / 940 / 950 / 960 / 970 / 980 / 990 / 1000

Extra small diameters: 10 / 12 / 15 / 17 / 19 / 22 / 24 / 26 / 28 / 30 / 32 / 34 / 36 / 38 / 40 / 42 / 44 / 46 / 48 / 50

Extra large diameters: 110 / 120 / 130 / 140 / 150 / 160 / 170 / 180 / 190 / 200 / 210 / 220 / 230 / 240 / 250 / 260 / 270 / 280 / 290 / 300 / 310 / 320 / 330 / 340 / 350 / 360 / 370 / 380 / 390 / 400 / 410 / 420 / 430 / 440 / 450 / 460 / 470 / 480 / 490 / 500 / 510 / 520 / 530 / 540 / 550 / 560 / 570 / 580 / 590 / 600 / 610 / 620 / 630 / 640 / 650 / 660 / 670 / 680 / 690 / 700 / 710 / 720 / 730 / 740 / 750 / 760 / 770 / 780 / 790 / 800 / 810 / 820 / 830 / 840 / 850 / 860 / 870 / 880 / 890 / 900 / 910 / 920 / 930 / 940 / 950 / 960 / 970 / 980 / 990 / 1000

Bearing No.	Boundary dimensions (mm)				Basic load ratings (kN)		Fatigue load factor		Limiting speeds (min-1)
	d	D	B	r (min)	Cr	C0r	Cu	f0	Grease lub.
W603 ZZ	3	9	5	0.15	0.54	0.16	4	14	60000

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3616060622976
Inside diameter	3 mm
Outside diameter	9 mm
Thickness	5 mm
Limiting speed	60000 rpm
Dynamic load	0.54 kN
Static load	0.16 kN
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE