

## Deep groove ball bearing single row W684-ZZ-JTEKT - W684-ZZ-JTEKT

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/single-row/w684-zz-jtekt>

Boundary dimensions

Open type    Shielded    Sealed    Locating snap ring

ZZ / 2RS / 2RD    NR

90 / 105 / 120 / 130 / 150 / 170 / 190 / 215 / 240 / 270 / 300 / 330 / 360 / 390 / 420 / 450 / 480 / 510 / 540 / 570 / 600 / 630 / 650 / 670 / 680 / 690 / 700 / 710 / 720 / 730 / 740 / 750 / 760 / 770 / 780 / 790 / 800 / 810 / 820 / 830 / 840 / 850 / 860 / 870 / 880 / 890 / 900 / 910 / 920 / 930 / 940 / 950 / 960 / 970 / 980 / 990 / 1000

Extruded Standard shielded ZZ

Bearing No.	Boundary dimensions (mm)				Basic load ratings (kN)		Fatigue load limit (kN)		Factor	Limiting speeds (min-1)
	d	D	B	r (min)	Cr	Cor	Cu	Cu2		
W684 ZZ	4	9	4	0.15	0.8	0.23	6	12.8		Grease Lub. 59000

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3616060623027
Inside diameter	4 mm
Sealing	Shield on both sides
Outside diameter	9 mm
Thickness	4 mm
Limiting speed	59000 rpm
Weight	1 g
Dynamic load	0.8 kN
Static load	0.23 kN
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE