

Deep groove ball bearing single row 687-JTEKT - 687-JTEKT

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/single-row/687-jtekt>

Boundary dimensions

Open type Shielded Sealed Locating snap ring

ZZ (2RU / 2RS / 2RD) NR

CR0 / CR1 / CR2 / CR3 / CR4 / CR5 / CR6 / CR7 / CR8 / CR9 / CR10 / CR11 / CR12 / CR13 / CR14 / CR15 / CR16 / CR17 / CR18 / CR19 / CR20 / CR21 / CR22 / CR23 / CR24 / CR25 / CR26 / CR27 / CR28 / CR29 / CR30 / CR31 / CR32 / CR33 / CR34 / CR35 / CR36 / CR37 / CR38 / CR39 / CR40 / CR41 / CR42 / CR43 / CR44 / CR45 / CR46 / CR47 / CR48 / CR49 / CR50 / CR51 / CR52 / CR53 / CR54 / CR55 / CR56 / CR57 / CR58 / CR59 / CR60 / CR61 / CR62 / CR63 / CR64 / CR65 / CR66 / CR67 / CR68 / CR69 / CR70 / CR71 / CR72 / CR73 / CR74 / CR75 / CR76 / CR77 / CR78 / CR79 / CR80 / CR81 / CR82 / CR83 / CR84 / CR85 / CR86 / CR87 / CR88 / CR89 / CR90 / CR91 / CR92 / CR93 / CR94 / CR95 / CR96 / CR97 / CR98 / CR99 / CR100

IMJ, Extra-small miniature (Cr) 405 / 410 / 415 / 420 / 425 / 430 / 435 / 440 / 445 / 450 / 455 / 460 / 465 / 470 / 475 / 480 / 485 / 490 / 495 / 500 / 505 / 510 / 515 / 520 / 525 / 530 / 535 / 540 / 545 / 550 / 555 / 560 / 565 / 570 / 575 / 580 / 585 / 590 / 595 / 600 / 605 / 610 / 615 / 620 / 625 / 630 / 635 / 640 / 645 / 650 / 655 / 660 / 665 / 670 / 675 / 680 / 685 / 690 / 695 / 700 / 705 / 710 / 715 / 720 / 725 / 730 / 735 / 740 / 745 / 750 / 755 / 760 / 765 / 770 / 775 / 780 / 785 / 790 / 795 / 800 / 805 / 810 / 815 / 820 / 825 / 830 / 835 / 840 / 845 / 850 / 855 / 860 / 865 / 870 / 875 / 880 / 885 / 890 / 895 / 900 / 905 / 910 / 915 / 920 / 925 / 930 / 935 / 940 / 945 / 950 / 955 / 960 / 965 / 970 / 975 / 980 / 985 / 990 / 995 / 1000

Extra-small standard open type

Bearing No.	Boundary dimensions (mm)				Basic load ratings (kN)		Fatigue load limit (kN)	factor	Limiting speeds (min-1)
	d	D	B	r (mm)	Cr	Cor			
687	7	14	3.5	0.15	1.45	0.51	0.01	14.2	45000

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250181085
Inside diameter	7 mm
Outside diameter	14 mm
Thickness	3.5 mm
Limiting speed	45000 rpm
Dynamic load	1.45 kN
Static load	0.51 kN
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE