

Tapered roller bearing 302-32-CR-JTEKT - 302-32-CR-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/302-32-cr-jtekt>

Boundary dimensions

Normal gradation: 30202UR, 30204UR, 30206UR, 30208UR, 30210UR, 30212UR, 30215UR, 30217UR, 30220UR, 30222UR, 30224UR, 30226UR, 30228UR, 30230UR, 30232UR, 30234UR, 30236UR, 30238UR, 30240UR, 30242UR, 30244UR, 30246UR, 30248UR, 30250UR, 30252UR, 30254UR, 30256UR, 30258UR, 30260UR, 30262UR, 30264UR, 30266UR, 30268UR, 30270UR, 30272UR, 30274UR, 30276UR, 30278UR, 30280UR, 30282UR, 30284UR, 30286UR, 30288UR, 30290UR, 30292UR, 30294UR, 30296UR, 30298UR, 30300UR

Medium gradation: 30202UR, 30204UR, 30206UR, 30208UR, 30210UR, 30212UR, 30215UR, 30217UR, 30220UR, 30222UR, 30224UR, 30226UR, 30228UR, 30230UR, 30232UR, 30234UR, 30236UR, 30238UR, 30240UR, 30242UR, 30244UR, 30246UR, 30248UR, 30250UR, 30252UR, 30254UR, 30256UR, 30258UR, 30260UR, 30262UR, 30264UR, 30266UR, 30268UR, 30270UR, 30272UR, 30274UR, 30276UR, 30278UR, 30280UR, 30282UR, 30284UR, 30286UR, 30288UR, 30290UR, 30292UR, 30294UR, 30296UR, 30298UR, 30300UR

Single row: 30202UR, 30204UR, 30206UR, 30208UR, 30210UR, 30212UR, 30215UR, 30217UR, 30220UR, 30222UR, 30224UR, 30226UR, 30228UR, 30230UR, 30232UR, 30234UR, 30236UR, 30238UR, 30240UR, 30242UR, 30244UR, 30246UR, 30248UR, 30250UR, 30252UR, 30254UR, 30256UR, 30258UR, 30260UR, 30262UR, 30264UR, 30266UR, 30268UR, 30270UR, 30272UR, 30274UR, 30276UR, 30278UR, 30280UR, 30282UR, 30284UR, 30286UR, 30288UR, 30290UR, 30292UR, 30294UR, 30296UR, 30298UR, 30300UR

Double row (TDO type): 40202, 40204, 40206, 40208, 40210, 40212, 40215, 40217, 40220, 40222, 40224, 40226, 40228, 40230, 40232, 40234, 40236, 40238, 40240, 40242, 40244, 40246, 40248, 40250, 40252, 40254, 40256, 40258, 40260, 40262, 40264, 40266, 40268, 40270, 40272, 40274, 40276, 40278, 40280, 40282, 40284, 40286, 40288, 40290, 40292, 40294, 40296, 40298, 40300

Four row: 40202, 40204, 40206, 40208, 40210, 40212, 40215, 40217, 40220, 40222, 40224, 40226, 40228, 40230, 40232, 40234, 40236, 40238, 40240, 40242, 40244, 40246, 40248, 40250, 40252, 40254, 40256, 40258, 40260, 40262, 40264, 40266, 40268, 40270, 40272, 40274, 40276, 40278, 40280, 40282, 40284, 40286, 40288, 40290, 40292, 40294, 40296, 40298, 40300

Primarily for use in the roll necks of rolling mills

Bearing No.	Boundary dimensions (mm)						Basic load ratings (kN)	Fatigue load limit (kN)	Limiting speed (min ⁻¹)
	d	D	B	r	1	2			
302/32CR	32	65	18.25	17	1	1	59.3 51.5	7.25	6200

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3616060628060
Inside diameter	32 mm
Outside diameter	65 mm
Thickness	18.25 mm
Limiting speed	6200 rpm
Dynamic load	59.3 kN
Static load	51.5 kN
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE