

## Tapered roller bearing 303-32-R-JTEKT - 303-32-R-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/303-32-r-jtekt>

Boundary dimensions

Single-row

Double-row

Four-row

Normal gradent

Medium gradent

Steep gradent

Double-row (TDO type)

Primarily for use in the roll necks of rolling mills.

Bearing No.	Boundary dimensions (mm)						Basic load ratings (kN)		Fatigue load limit (kN)	Limiting speeds (min <sup>-1</sup> )
	d	D	B	r1 (max)	r2 (max)	r3 (max)	C <sub>r</sub>	C <sub>0r</sub>	C <sub>0</sub>	Cr/3000 L <sub>10</sub>
303/32R	32	75	21.75	1.5	1.5	1.5	80.5	65.6	9.9	5500

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3616060628091
Inside diameter	32 mm
Inside diameter	1.26" inch
Outside diameter	75 mm
Outside diameter	2.953" inch
Thickness	21.75 mm
Thickness	0.856" inch
Limiting speed	5500 rpm
Dynamic load	80.5 kN
Static load	65.6 kN
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE