


## Tapered roller bearing 452-950-JTEKT - 452-950-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/452-950-jtekt>

Boundary dimensions



| Bearing No.    | Boundary dimensions(mm) |      |     |         |         |    | Basic load ratings(kN) |    | Fatigue load limit(kN) | Limiting speeds(min-1) |
|----------------|-------------------------|------|-----|---------|---------|----|------------------------|----|------------------------|------------------------|
|                | d                       | D    | T   | r1(min) | r1(max) | Cr | C0r                    | Cu | Grease lub.            |                        |
| <b>452/950</b> | 950                     | 1360 | 300 | 7.5     | 7.5     | -  | 24900                  | -  | -                      |                        |

### PRODUCT FEATURES

|                  |               |
|------------------|---------------|
| Brand            | JTEKT         |
| N° Ean13         | 3616060628664 |
| Inside diameter  | 950 mm        |
| Inside diameter  | 37.402" inch  |
| Outside diameter | 1360 mm       |
| Outside diameter | 53.543" inch  |
| Thickness        | 300 mm        |
| Thickness        | 11.811" inch  |
| Static load      | 24900 kN      |
| Packaging        | 1             |

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE