

Deep groove ball bearing single row 23048-RR-JTEKT - 23048-RR-JTEKT

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/single-row/23048-rr-jtekt>

Boundary dimensions

Asymmetrical rollers: R,RR
Symmetrical rollers: R,LR,RR, R,RA
Taper bore: R,TR,30

23048RR / 23048RRJRH1 / 23048RRJRH2 / 23048RRJRH3 / 23048RRJRH4 / 23048RRJRH5 / 23048RRJRH6 / 23048RRJRH7 / 23048RRJRH8 / 23048RRJRH9 / 23048RRJRH10 / 23048RRJRH11 / 23048RRJRH12 / 23048RRJRH13 / 23048RRJRH14 / 23048RRJRH15 / 23048RRJRH16 / 23048RRJRH17 / 23048RRJRH18 / 23048RRJRH19 / 23048RRJRH20 / 23048RRJRH21 / 23048RRJRH22 / 23048RRJRH23 / 23048RRJRH24 / 23048RRJRH25 / 23048RRJRH26 / 23048RRJRH27 / 23048RRJRH28 / 23048RRJRH29 / 23048RRJRH30 / 23048RRJRH31 / 23048RRJRH32 / 23048RRJRH33 / 23048RRJRH34 / 23048RRJRH35 / 23048RRJRH36 / 23048RRJRH37 / 23048RRJRH38 / 23048RRJRH39 / 23048RRJRH40 / 23048RRJRH41 / 23048RRJRH42 / 23048RRJRH43 / 23048RRJRH44 / 23048RRJRH45 / 23048RRJRH46 / 23048RRJRH47 / 23048RRJRH48 / 23048RRJRH49 / 23048RRJRH50 / 23048RRJRH51 / 23048RRJRH52 / 23048RRJRH53 / 23048RRJRH54 / 23048RRJRH55 / 23048RRJRH56 / 23048RRJRH57 / 23048RRJRH58 / 23048RRJRH59 / 23048RRJRH60 / 23048RRJRH61 / 23048RRJRH62 / 23048RRJRH63 / 23048RRJRH64 / 23048RRJRH65 / 23048RRJRH66 / 23048RRJRH67 / 23048RRJRH68 / 23048RRJRH69 / 23048RRJRH70 / 23048RRJRH71 / 23048RRJRH72 / 23048RRJRH73 / 23048RRJRH74 / 23048RRJRH75 / 23048RRJRH76 / 23048RRJRH77 / 23048RRJRH78 / 23048RRJRH79 / 23048RRJRH80 / 23048RRJRH81 / 23048RRJRH82 / 23048RRJRH83 / 23048RRJRH84 / 23048RRJRH85 / 23048RRJRH86 / 23048RRJRH87 / 23048RRJRH88 / 23048RRJRH89 / 23048RRJRH90 / 23048RRJRH91 / 23048RRJRH92 / 23048RRJRH93 / 23048RRJRH94 / 23048RRJRH95 / 23048RRJRH96 / 23048RRJRH97 / 23048RRJRH98 / 23048RRJRH99 / 23048RRJRH100

Spherical roller bearings

Bearing No.	Boundary dimensions(mm)			n(min)	Basic load ratings(kN)			Fatigue load limit(kN)	Limiting speeds(min-1)
	d	D	B		Cr	C0r	Cu		
23048RR	240	360	92	3	1480	2190	161	860	

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3616060670816
Inside diameter	240 mm
Outside diameter	360 mm
Thickness	92 mm
Limiting speed	860 rpm
Dynamic load	1480 kN
Static load	2190 kN
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE