

Deep groove ball bearing single row 22264-R-JTEKT - 22264-R-JTEKT

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/single-row/22264-r-jtekt>

Boundary dimensions

Asymmetrical rollers: RJR
Symmetrical rollers: RJR/R, RHA
Taper bore: KøK30

22800R / 23000R/RH/RHA / 23200R/RH/RHA / 23300R/RH/RHA / 23400R/RH/RHA / 23500R/RH/RHA / 23600R/RH/RHA / 23700R/RH/RHA / 23800R/RH/RHA / 23900R/RH/RHA / 24000R/RH/RHA / 24100R/RH/RHA / 24200R/RH/RHA / 24300R/RH/RHA / 24400R/RH/RHA / 24500R/RH/RHA / 24600R/RH/RHA / 24700R/RH/RHA / 24800R/RH/RHA / 24900R/RH/RHA / 25000R/RH/RHA / 25100R/RH/RHA / 25200R/RH/RHA / 25300R/RH/RHA / 25400R/RH/RHA / 25500R/RH/RHA / 25600R/RH/RHA / 25700R/RH/RHA / 25800R/RH/RHA / 25900R/RH/RHA / 26000R/RH/RHA / 26100R/RH/RHA / 26200R/RH/RHA / 26300R/RH/RHA / 26400R/RH/RHA / 26500R/RH/RHA / 26600R/RH/RHA / 26700R/RH/RHA / 26800R/RH/RHA / 26900R/RH/RHA / 27000R/RH/RHA / 27100R/RH/RHA / 27200R/RH/RHA / 27300R/RH/RHA / 27400R/RH/RHA / 27500R/RH/RHA / 27600R/RH/RHA / 27700R/RH/RHA / 27800R/RH/RHA / 27900R/RH/RHA / 28000R/RH/RHA / 28100R/RH/RHA / 28200R/RH/RHA / 28300R/RH/RHA / 28400R/RH/RHA / 28500R/RH/RHA / 28600R/RH/RHA / 28700R/RH/RHA / 28800R/RH/RHA / 28900R/RH/RHA / 29000R/RH/RHA / 29100R/RH/RHA / 29200R/RH/RHA / 29300R/RH/RHA / 29400R/RH/RHA / 29500R/RH/RHA / 29600R/RH/RHA / 29700R/RH/RHA / 29800R/RH/RHA / 29900R/RH/RHA / 30000R/RH/RHA

Spherical roller bearings

Bearing No.	Boundary dimensions(mm)				Basic load ratings(kN)		Fatigue load limit(kN)	Limiting speeds(min-1)
	d	D	B	n(min)	Cr	C0r	C0r Grease lub.	
22264R	320	580	150	5	3420	4540	385	490

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3616060671615
Inside diameter	320 mm
Inside diameter	12.598" inch
Outside diameter	580 mm
Outside diameter	22.835" inch
Thickness	150 mm
Thickness	5.906" inch
Limiting speed	490 rpm
Dynamic load	3420 kN
Static load	4540 kN
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE