

## **Roller chain simplex**

# **ANSI60-1-ELITE-DIN8188-5M-IWIS - ANSI60-1-ELITE-DIN8188-5M-IWIS**

<https://www.123bearing.eu/power-transmission/roller-chain/simplex/ansi60-1-elite-din8188-5m-iwis>



## **PRODUCT FEATURES**

|                                |                      |
|--------------------------------|----------------------|
| Brand                          | IWIS                 |
| N° Ean13                       | 3616060999603        |
| Type                           | 60                   |
| Lubrication                    | elidurplus           |
| Packaging                      | 5m                   |
| Chain standards                | iso606ansi           |
| ISO standard breaking load     | 31.3 kN              |
| Weight per meter               | 1.5 kg               |
| Joint surface                  | 1.05 cm <sup>2</sup> |
| Pitch                          | 19.05 mm             |
| Pitch                          | 3/4" inch            |
| Width between inner plates     | 12.57 mm             |
| Width between inner plates     | 0.495" inch          |
| Roller diameter                | 11.91 mm             |
| Roller diameter                | 15/32" inch          |
| Axis diameter                  | 5.96 mm              |
| Axis diameter                  | 0.235" inch          |
| Plate thickness inside outside | 2,40/2,40            |
| Plate height                   | 18.1 mm              |
| Plate height                   | 0.713" inch          |
| Additional length              | 4.6 mm               |
| Additional length              | 0.181" inch          |
| number of rows                 | 1                    |

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE