


Drawn cup roller bearing BA1610-ZOH-IKO - BA1610-ZOH-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/drawn-cup/ba1610-zoh-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



BA--Z BHA--Z

Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g
	Standard	Mass (Ref.) g	Closed end									
25.400 (1)	--	--	--	BA 1610 Z	22	--	--	--	--	--	--	--

Boundary dimensions			Standard mounting dimensions			Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*)	Assembled inner ring
F _w	D	C	Shaft dia. h ₈	Housing bore dia. j7	mm				
25.400	31.750	15.881	25.400	25.387	31.764	11 900	18 100	15 000	--

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952172804
Inside diameter	25.4 mm
Inside diameter	1" inch
Outside diameter	31.75 mm
Outside diameter	1 1/4" inch
Thickness	15.88 mm
Thickness	5/8" inch
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE