


Drawn cup roller bearing BAM1010-IKO - BAM1010-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/drawn-cup/bam1010-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
15.875 (5/8)	—	—	—	—	—	—	—	BAM 1010	12	—	—

Boundary dimensions			Standard mounting dimensions				Basic dynamic load rating	Basic static load rating	Allowable rotational speed ^(*)	Assembled inner ring	
F_w	D	C	Shaft dia. h8		Housing bore dia. J7		C	C_0	rpm		
			Max.	Min.	Max.	Min.	N	N			
15.875 / 2	20.638 / 2	15.88 / 2	15.88	15.875	15.884	15.875	20.650 / 20.629	7 320	10 700	25 000	—

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952172897
Inside diameter	15.88 mm
Inside diameter	5/8" inch
Outside diameter	20.64 mm
Outside diameter	13/16" inch
Thickness	15.88 mm
Thickness	5/8" inch
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE