Drawn cup roller bearing
BAM1014-IKO - BAM1014-IKO

https://www.123bearing.eu/bearing-housing/needle-roller-bearing/drawn-cup/bam1014-iko



IKO

SHELL TYPE NEEDLE ROLLER BEARINGS

Inch Series

BAM BHAM

Shaft dia. mm (inch)	Identification number									
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained	Mass (Ref.) g
15.875 (5/8)	—	—	—	—	—	—	BAM 1014	16.2	—	—
	—	—	—	—	—	—	—	—	—	—

Boundary dimensions mm(inch)				Standard mounting dimensions mm				Basic dynamic load rating	Basic static load rating	Allowable rotational speed(*)	Assembled inner ring
				Shaft dia. h6		Housing bore dia. J7					
F_w	D	C	r_{2} Max.	Max.	Min.	Max.	Min.	C N	C_0 N	rpm	
15.875 (5/8)	20.638 (13/16)	22.22 (.875)	1.3	15.875	15.864	20.650	20.629	10 700	17 500	25 000	IRB 714

Note(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952172910
Inside diameter	15.88 mm
Outside diameter	20.64 mm
Thickness	22.22 mm
Packaging	1

contact@123bearing.eu
+33 359 36 04 90
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE