


## Drawn cup roller bearing BAM1210-IKO - BAM1210-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/drawn-cup/bam1210-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series



Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
<b>19.050</b> (3/4)	—	—	—	—	—	—	—	<b>BAM 1210</b>	18.6	—	—
Boundary dimensions mm(inch)		Standard mounting dimensions mm				Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(1)</sup>	Assembled inner ring		
<i>F<sub>w</sub></i>	<i>D</i>	<i>C</i>	Shaft dia. <i>d</i>		Housing bore dia. <i>J7</i>	N	N	rpm	IRB #10-1		
19.050	25.400	15.881 (625)	1.3	Max. 19.050 Min. 19.037	Max. 25.412 Min. 25.391	9 500	13 200	20 000			

Note<sup>(1)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952173009
Inside diameter	19.05 mm
Outside diameter	25.4 mm
Thickness	15.88 mm
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE