


## Drawn cup roller bearing BAM1216-IKO - BAM1216-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/drawn-cup/bam1216-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series



Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g	Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end										
19.050 (3/4)	---	---	---	---	---	---	---	---	---	---	---	---	---
Boundary dimensions		mm(inch)		Standard mounting dimensions		mm		Basic dynamic load rating		Basic static load rating		Allowable rotational speed <sup>(1)</sup>	
$F_w$	$D$	$C$	$\phi$	Shaft dia. h6 Max.   Min.	Housing bore dia. J7 Max.   Min.	$C$	$C_0$	$C$	$C_0$	$C$	$C_0$	rpm	Assembled inner ring
19.050   3/4	25.400   1	25.40   1.000	1.3	19.050   19.037	25.412   25.391	16 300	26 500	20 000	IRB 816-1				

Note<sup>(1)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952173030
Inside diameter	19.05 mm
Outside diameter	25.4 mm
Thickness	25.4 mm
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE