


Drawn cup roller bearing BAM1310-IKO - BAM1310-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/drawn-cup/bam1310-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



BAM BHAM

Shaft dia. mm (inch)	Identification number			Identification number			Grease retained Mass (Ref.) g	Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end	Standard	Mass (Ref.) g	Closed end		
20.638 ($\frac{3}{16}$)	—	—	—	—	—	BAM 1310	20	—

Boundary dimensions			Standard mounting dimensions				Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring
F _w	D	C	Shaft dia. h6	Housing bore dia. J7	Max.	Min.				
20.638 $\frac{3}{16}$	26.988 $1 \frac{1}{16}$	15.881 $\frac{5}{16}$	20.638	20.625	27.000	26.979	9 870	14 200	19 000	IRB 910

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952173061
Inside diameter	20.64 mm
Outside diameter	26.99 mm
Thickness	15.88 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE