

Drawn cup roller bearing BAM1314-IKO - BAM1314-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/drawn-cup/bam1314-iko>

SHELL TYPE NEEDLE ROLLER BEARINGS

Inch Series

BAM BHAM

Identification number													
Shaft dia. mm (inch)	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained	Mass (Ref.) g			
20.638 ($\frac{1}{2}$)	—	—	—	—	—	—	BAM 1314	27	—	—			
Boundary dimensions mm(inch)				Standard mounting dimensions mm			Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring			
F _w	D	C	H	Shaft dia. h6 Max. Min.	Housing bore J7 Max. Min.	N	C	C ₀	N	IRB			
20.638 $\frac{1}{2}$	26.988 $\frac{1}{2}$	22.22 $\frac{1}{2}$	.875	1.3	20.638	20.625 27.000	26.979	14 700	23 800	19 000	IRB 914		

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952173085
Inside diameter	20.64 mm
Outside diameter	26.99 mm
Thickness	22.22 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE