


Drawn cup roller bearing BAM1320-IKO - BAM1320-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/drawn-cup/bam1320-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
20.638 ($\frac{3}{16}$)	—	—	—	—	—	—	—	BAM 1320	37.5	—	—
Boundary dimensions mm(inch)		Standard mounting dimensions mm				Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽¹⁾	Assembled inner ring		
F_w	D	C	d_2	Shaft dia. d_6	Housing bore dia. J_7	N	N	rpm			
20.638 $\frac{3}{16}$	26.988 $1 \frac{1}{8}$	31.751 1.250	1.3	20.638 Max.	20.625 Min.	27.000 Max.	26.979 Min.	21 200	38 100	19 000	IRB 920

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952173108
Inside diameter	20.64 mm
Outside diameter	26.99 mm
Thickness	31.75 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE