


Drawn cup roller bearing BAM1414-IKO - BAM1414-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/drawn-cup/bam1414-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g	Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end										
22.225 (7/8)	---	---	---	---	---	---	---	---	---	---	---	---	---
Boundary dimensions		mm(inch)		Standard mounting dimensions		mm		Basic dynamic load rating		Basic static load rating		Allowable rotational speed ⁽¹⁾	
F_w	D	C	h_6	Shaft dia. Max.	Housing bore dia. Min.	C	C_0	N	N	rpm	Assembled inner ring		
22.225 (7/8)	28.575 (1 1/4)	22.22 (.875)	2.8	22.225 Max.	22.212 Min.	28.587	28.566	15 900	25 500	18 000	IRB 1014		

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952173146
Inside diameter	22.23 mm
Outside diameter	28.58 mm
Thickness	22.22 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE