


Drawn cup roller bearing BAM146-IKO - BAM146-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/drawn-cup/bam146-iko>

IKO

SHELL TYPE NEEDLE ROLLER BEARINGS

Inch Series



BAM BHAM

Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained g	Mass (Ref.) g				
	Standard	Mass (Ref.) g	Closed end														
22.225 ($\frac{7}{8}$)	---	---	---	---	---	---	---	---	---	---	---	---	---				
Boundary dimensions		mm(inch)		Standard mounting dimensions				mm		Basic dynamic load rating		Basic static load rating		Allowable rotational speed ⁽¹⁾		Assembled inner ring	
F_w	D	C	B	Shaft dia. h6		Housing bore dia. J7		Max.		Min.		N		N		rpm	
22.225	28.575	9.521	2.8	22.225	22.212	28.587	28.566	5 430	6 740	18 000	IRB 106						

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952173184
Inside diameter	22.23 mm
Outside diameter	28.58 mm
Thickness	9.52 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE