


Drawn cup roller bearing BAM1910-IKO - BAM1910-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/drawn-cup/bam1910-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
30.162 (1 1/8)	—	—	—	—	—	—	—	BAM 1910	37.5	—	—
Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*)	Assembled inner ring	
F _w	D	C	t	Shaft dia. h _s	Housing bore dia. J7	Max.	Min.	N	N	rpm	—
30.162 (1 1/8)	38.100 (1 1/2)	15.88 (5/8)	2.8	30.162 (30.146)	38.114	38.089		15 000	22 500	12 000	—

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952173382
Inside diameter	30.16 mm
Outside diameter	38.1 mm
Thickness	15.88 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE