


Drawn cup roller bearing BAM208-IKO - BAM208-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/drawn-cup/bam208-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
31.750 (1 1/4)	---	---	---	---	---	---	---	BAM 208	26	---	---
Boundary dimensions mm(inch)		Standard mounting dimensions mm				Basic dynam. load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*)	Assembled inner ring		
F _w	D	C ₁	h _s Max.	h _s Min.	J ₇ Max.	J ₇ Min.	N	N	rpm		
31.750 (1 1/4)	38.100 (1 1/2)	12.70 (500)	2.8	31.750	31.734	38.114	38.089	9 100	14 700	12 000	IRB 168

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952173405
Inside diameter	31.75 mm
Inside diameter	1 1/4" inch
Outside diameter	38.1 mm
Outside diameter	1 1/2" inch
Thickness	12.7 mm
Thickness	1/2" inch
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE