


Drawn cup roller bearing BAM95-IKO - BAM95-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/drawn-cup/bam95-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number								
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g
14.288 ($\frac{9}{16}$)	—	—	—	—	—	—	BAM 95	5.8	—

Boundary dimensions			Standard mounting dimensions			Basic dynamic load rating C ₀	Basic static load rating C ₀	Allowable rotational speed ^(*)	Assembled inner ring
F _w	D	C	Shaft dia. h8	Housing bore dia. J7	C				
14.288 $\frac{9}{16}$	19.050 $\frac{3}{4}$	7.92 0.312	14.288 0.562	14.277 0.562	19.062 0.751	2 780	2 970	30 000	—

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952173641
Inside diameter	14.29 mm
Inside diameter	9/16" inch
Outside diameter	19.05 mm
Outside diameter	3/4" inch
Thickness	7.92 mm
Thickness	0.312" inch
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE