


Drawn cup roller bearing BAM96-IKO - BAM96-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/drawn-cup/bam96-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number								
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g
14.288 ($\frac{9}{16}$)	—	—	—	—	—	—	BAM 96	6.8	—

Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating	Basic static load rating	Allowable rotational speed ⁽¹⁾	Assembled inner ring
F_w	D	C	Shaft dia. h8		Housing bore dia. J7		C	C_0	rpm	
			Max.	Min.	Max.	Min.	N	N		
14.288 ($\frac{9}{16}$)	19.050 ($\frac{3}{4}$)	9.52 ($\frac{3}{8}$)	14.288	14.277	19.062	19.041	3 850	4 560	30 000	—

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952173658
Inside diameter	14.29 mm
Outside diameter	19.05 mm
Thickness	9.52 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE