

Tapered roller bearing 30240J2-SKF - 30240J2-SKF

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/30240j2-skf>

Dimensions d'encadrement			Charges de base		Vitesses de base		Désignation
d	D	T	C	C ₀	Vitesse de référence	Vitesse limite	* Roulement SKF Explorer
mm			kN		tr/min		
200	360	64	792	1120	1300	1700	30240 J2

Technical drawing showing dimensions and coefficients of calculation for the tapered roller bearing 30240J2-SKF. The drawing includes dimensions for the inner ring, outer ring, and rollers, as well as coefficients of calculation (Y₁, Y₂, Y₀).

Dimensions shown in the drawing:
 - Inner diameter: $\varnothing 200$
 - Outer diameter: $\varnothing 360$
 - Thickness: $T = 64$
 - Dynamic load rating: $C = 792$
 - Static load rating: $C_0 = 1120$
 - Reference speed: $v_{ref} = 1300$ tr/min
 - Limit speed: $v_{lim} = 1700$ tr/min
 - Coefficients of calculation: $Y_1 = 0.43$, $Y_2 = 1.4$, $Y_0 = 0.8$

PRODUCT FEATURES

Brand	SKF
N° Ean13	3663952236179
Inside diameter	200 mm
Inside diameter	7.874" inch
Outside diameter	360 mm
Outside diameter	14.173" inch
Thickness	64 mm
Thickness	2.52" inch
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE