

## Tapered roller bearing 30232J2-SKF - 30232J2-SKF

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/30232j2-skf>

Dimensions d'encombrement			Charges de base		Vitesses de base		Désignation
d	D	T	C	C <sub>0</sub>	Vitesse de référence	Vitesse limite	* Roulement SKF Explorer
mm			kN		tr/min		
160	290	52	528	735	1600	3200	30232 J2

  

Technical drawing showing dimensions and load ratings for the tapered roller bearing. Dimensions include: d = 160 mm, D = 290 mm, T = 52 mm, C = 40 mm, B = 48 mm, r<sub>1</sub> min 4 mm, r<sub>2</sub> min 3 mm, r<sub>3</sub> min 3 mm, r<sub>4</sub> min 3 mm, r<sub>5</sub> min 3 mm, r<sub>6</sub> min 3 mm, r<sub>7</sub> min 3 mm, r<sub>8</sub> min 3 mm, r<sub>9</sub> min 3 mm, r<sub>10</sub> min 3 mm, r<sub>11</sub> min 3 mm, r<sub>12</sub> min 3 mm, r<sub>13</sub> min 3 mm, r<sub>14</sub> min 3 mm, r<sub>15</sub> min 3 mm, r<sub>16</sub> min 3 mm, r<sub>17</sub> min 3 mm, r<sub>18</sub> min 3 mm, r<sub>19</sub> min 3 mm, r<sub>20</sub> min 3 mm, r<sub>21</sub> min 3 mm, r<sub>22</sub> min 3 mm, r<sub>23</sub> min 3 mm, r<sub>24</sub> min 3 mm, r<sub>25</sub> min 3 mm, r<sub>26</sub> min 3 mm, r<sub>27</sub> min 3 mm, r<sub>28</sub> min 3 mm, r<sub>29</sub> min 3 mm, r<sub>30</sub> min 3 mm, r<sub>31</sub> min 3 mm, r<sub>32</sub> min 3 mm, r<sub>33</sub> min 3 mm, r<sub>34</sub> min 3 mm, r<sub>35</sub> min 3 mm, r<sub>36</sub> min 3 mm, r<sub>37</sub> min 3 mm, r<sub>38</sub> min 3 mm, r<sub>39</sub> min 3 mm, r<sub>40</sub> min 3 mm, r<sub>41</sub> min 3 mm, r<sub>42</sub> min 3 mm, r<sub>43</sub> min 3 mm, r<sub>44</sub> min 3 mm, r<sub>45</sub> min 3 mm, r<sub>46</sub> min 3 mm, r<sub>47</sub> min 3 mm, r<sub>48</sub> min 3 mm, r<sub>49</sub> min 3 mm, r<sub>50</sub> min 3 mm, r<sub>51</sub> min 3 mm, r<sub>52</sub> min 3 mm, r<sub>53</sub> min 3 mm, r<sub>54</sub> min 3 mm, r<sub>55</sub> min 3 mm, r<sub>56</sub> min 3 mm, r<sub>57</sub> min 3 mm, r<sub>58</sub> min 3 mm, r<sub>59</sub> min 3 mm, r<sub>60</sub> min 3 mm, r<sub>61</sub> min 3 mm, r<sub>62</sub> min 3 mm, r<sub>63</sub> min 3 mm, r<sub>64</sub> min 3 mm, r<sub>65</sub> min 3 mm, r<sub>66</sub> min 3 mm, r<sub>67</sub> min 3 mm, r<sub>68</sub> min 3 mm, r<sub>69</sub> min 3 mm, r<sub>70</sub> min 3 mm, r<sub>71</sub> min 3 mm, r<sub>72</sub> min 3 mm, r<sub>73</sub> min 3 mm, r<sub>74</sub> min 3 mm, r<sub>75</sub> min 3 mm, r<sub>76</sub> min 3 mm, r<sub>77</sub> min 3 mm, r<sub>78</sub> min 3 mm, r<sub>79</sub> min 3 mm, r<sub>80</sub> min 3 mm, r<sub>81</sub> min 3 mm, r<sub>82</sub> min 3 mm, r<sub>83</sub> min 3 mm, r<sub>84</sub> min 3 mm, r<sub>85</sub> min 3 mm, r<sub>86</sub> min 3 mm, r<sub>87</sub> min 3 mm, r<sub>88</sub> min 3 mm, r<sub>89</sub> min 3 mm, r<sub>90</sub> min 3 mm, r<sub>91</sub> min 3 mm, r<sub>92</sub> min 3 mm, r<sub>93</sub> min 3 mm, r<sub>94</sub> min 3 mm, r<sub>95</sub> min 3 mm, r<sub>96</sub> min 3 mm, r<sub>97</sub> min 3 mm, r<sub>98</sub> min 3 mm, r<sub>99</sub> min 3 mm, r<sub>100</sub> min 3 mm.

Coefficients de calcul:  
 $\alpha = 0.43$   
 $\gamma = 1.4$   
 $\gamma_0 = 0.8$

### PRODUCT FEATURES

Brand	SKF
N° Ean13	7316577327062
Inside diameter	160 mm
Inside diameter	6.299" inch
Outside diameter	290 mm
Outside diameter	11.417" inch
Thickness	52 mm
Thickness	2.047" inch
Weight	13200 g
Packaging	1
Standard	No standard

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE