

## Roller bearing NCF2940CV-SKF - NCF2940CV-SKF

<https://www.123bearing.eu/bearing-housing/roller-bearing/roller/ncf2940cv-skf>

Dimensions d'encadrement			Charges de base		Vitesses de base		Désignation
d	D	B	dynamique C	statique C <sub>0</sub>	Vitesse de référence tr/min	Vitesse limite	
mm			kN				
200	280	48	528	965	1000	1300	NCF 2940 CV

  

The technical drawing shows the bearing with the following dimensions: D = 280 mm, d = 200 mm, B = 48 mm, E = 263 mm, D<sub>1</sub> = 253 mm, d<sub>1</sub> = 226,5 mm, r<sub>1</sub> = 2,5 mm, r<sub>2</sub> = 2,5 mm, r<sub>3</sub> = 3 mm, D<sub>max</sub> = 269 mm, D<sub>min</sub> = 269 mm, D<sub>max</sub> = 269 mm, D<sub>min</sub> = 211 mm, D<sub>max</sub> = 222 mm, r<sub>max</sub> = 2 mm. Coefficients de calcul: k<sub>r</sub> = 0,2, k<sub>a</sub> = 0,3, Y = 0,4.

### PRODUCT FEATURES

Brand	SKF
N° Ean13	7316572343302
Inside diameter	200 mm
Outside diameter	280 mm
Thickness	48 mm
Limiting speed	1300 rpm
Weight	9110 g
Dynamic load	528 kN
Static load	965 kN
Packaging	-
Standard	-

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE