


## Tapered roller bearing 1674-1620-TIMKEN - 1674-1620-TIMKEN

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/1674-1620-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**



Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width B	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> e	Dynamic <sup>(1)</sup> C <sub>2</sub>	Factor <sup>(2)</sup> e <sub>2</sub>	Static C <sub>0</sub>	Inner	Outer	
mm	mm	mm	N		N	N	N			
31.623	66.675	20.638	3250	0.37	13000	8950	1.57	12000	1674	
1.2493	2.6250	0.8125	11800		3800	1950		13000	1620	

Bearing Dimensions										Geometry Factors			Bearing Weight	
Width		ER. Dr. μm	Shaft		Housing		Cage		G <sub>1</sub>	G <sub>2</sub>	C <sub>3</sub>			
B	C		Max Shaft Fillet Radius R <sub>1</sub>	Backing Shoulder Dia. d <sub>s</sub>	Max Housing Fillet Radius r <sub>1</sub>	Backing Shoulder Dia. D <sub>s</sub>	A <sub>1</sub> <sup>(1)</sup>	A <sub>2</sub> <sup>(1)</sup>						
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg	
20.638	15.875	-5.3	1.5	37.8	35.5	1.5	61.0	58.0	1.5	1.1	16.6	0.7	0.9644	0.33
0.8125	0.6250	-0.21	0.06	1.46	1.36	0.06	2.40	2.28	0.06	0.05				0.72

### PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	3663952309941
Inside diameter	31.62 mm
Outside diameter	66.68 mm
Thickness	20.64 mm
Weight	200 g
Packaging	1
Standard	No standard

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE